



ClearGuard

Disabled Toilet Access Control System

Make access to disabled toilets easier with the ClearGuard toilet access control system.

ClearGuard consists of an external panel with an OPEN/ CLOSE button and occupancy indicator. An internal panel allows the user to OPEN/LOCK the toilet door.



- Designed for Ease of Use**
 Large, but slim illuminated switch design with “Door Opening” & “Door Closing” sound prompts. External switch indicates when the toilet is in use
- User Safety Prioritised**
 Emergency door opening from the outside in the event of a user needing assistance. Audio alert when batteries need replacement
- Wireless or Hardwired**
 Available in hardwired or 433MHz wireless version for reduced installation time and installation disturbance
- Water Resistant**
 IP54 water and dust resistant



ClearGuard



Technical Specification

Accessories



External Switch CGE-Tx



Internal Switch CGI-Tx



Receiver (CG-Rx)

Receiver (CG-Rx)

Power	DC12-30V / AC12-24V
Relay Contact Capacity	1A/30VDC, 0.5A / 125VDC
Operating Temperature	-20°C to +50°C
Product Size	150 x 43 x 25mm
Current Consumption	Standby: 20mA / Action: 80mA (DC 24V)

Internal Switch CGI-Tx / External Switch CGE-Tx

Rated Frequency	FM 433.92MHz
Battery	1.5V AA 4EA Each
Operating Temperature	-20°C to +50°C
Product Size	135 x 135 x 19mm
International Protection	IP54 (Waterproof)

Equipment Provided

Receiver (CG-Rx)	x 1
Internal Switch CGI-Tx / External Switch CGE-Tx	x 1 each
Power Connector	x1 (grey)
Output Contact Connector	x 1 (green)
3M Stickers	x 4
1.5V AA Size Batteries	x 8
Manual	x 1

Dimensions

